

(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

**EP 0 384 509 B1**

(12)

**EUROPEAN PATENT SPECIFICATION**

(45) Date of publication and mention  
of the grant of the patent:  
**02.05.1997 Bulletin 1997/18**

(51) Int Cl.<sup>6</sup>: **G06F 3/033**

(21) Application number: **90200268.2**

(22) Date of filing: **07.02.1990**

(54) **Display device with input function**

Anzeigegerät mit Eingabefunktion

Dispositif de visualisation avec une fonction pour l'entrée de données

(84) Designated Contracting States:  
**DE FR GB IT NL**

• **Sato, Yoshikazu**  
**NL-5656 AA Eindhoven (NL)**

(30) Priority: **13.02.1989 JP 33195/89**

(74) Representative: **Raap, Adriaan Yde et al**  
**INTERNATIONAAL OCTROOIBUREAU B.V.,**  
**Prof. Holstlaan 6**  
**5656 AA Eindhoven (NL)**

(43) Date of publication of application:  
**29.08.1990 Bulletin 1990/35**

(73) Proprietor: **Philips Electronics N.V.**  
**5621 BA Eindhoven (NL)**

(56) References cited:  
**US-A- 4 345 248**                      **US-A- 4 655 552**  
**US-A- 4 679 909**

(72) Inventors:  
• **Tanigaki, Yasushi**  
**NL-5656 AA Eindhoven (NL)**

**EP 0 384 509 B1**

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

## Description

The invention relates to a display device comprising a first substrate provided with pixel electrodes and active switching elements for driving said picture electrodes, photosensitive elements comprising at least one semiconductor material of the active elements and a group of read-out electrodes and a display material sandwiched between the first substrate and a second substrate opposing the first substrate.

The invention is used in a display device in which an input function is incorporated.

More specifically, the present invention is used to a flat-type display device with an input function in which a liquid crystal material, an electrochrome material or the like is used. Such a display device with an input function is suitable for use as a device for the purpose of education or office automation, such as a combination of a CRT display device with a light pen, wherein information displayed on the screen can be selected at its displaced position and sent to another device, or wherein information of a display position on the screen can directly be input.

A liquid-crystal type display device in which an input function with the aid of light is incorporated is known, from US-A-4 655 552.

In such a display device signal electrodes are provided on a substrate which is disposed on one side of a liquid crystal material. Another substrate disposed on the other side of the liquid crystal material is provided with active elements, read-out electrodes, photo-sensitive elements, and scan electrodes both for the photo-sensitive electrodes and the read-out electrodes.

With the display device of the above-described type, a substantial number of electrodes such as the data-electrodes, the scan electrodes for the photo-sensitive elements and the read-out electrodes must be provided on the same substrate in addition to the active elements and the photo-sensitive elements. Therefore the process for the fabrication of the display device is complicated and the yield rate of the products is low, particularly, since the read-out electrodes and the scanning electrodes cross each other so cross-overs have to be provided in the case of the device shown in US-A-4 655 552. Moreover, since the scan electrodes for the display function and those for the photo-sensitive input function are separated from each other, this display device has a disadvantage that a circuit for driving the above electrodes is complicated.

It is therefore one of the objects of the present invention to provide a display device, with an input function, in which the structure of a circuit on the substrate is simple so that the process for fabrication can be simplified and that a high yield rate of products can be obtained.

It is another object of the invention to provide such a display device which is capable of displaying a color picture.

Therefore, according to the present invention a display device as mentioned in the opening paragraph is characterized in that each photosensitive element is related to a predetermined number of pixel electrodes and the first substrate is further provided with a group of signal electrodes, which extend in either a row or a column direction of the pixel electrodes and are connected thereto via said switching elements and which extend in the same direction as the read-out electrodes, the second substrate being provided with a group of scan electrodes which extend in a direction perpendicular to the direction in which said signal electrodes extend, scan electrodes being common to the photo-sensitive elements and pixels.

The scan electrodes for the active elements and those for the photo-sensitive elements are now provided on a substrate other than the substrate on which the above elements are formed and, in addition, the two groups of scan electrodes are combined into one group of common scan electrodes and formed on said other substrate, whereby the circuits on the respective substrata are simplified.

A device in which the signal electrodes and read-out electrodes extend in the same direction perpendicular to the scanning electrodes is known per se from US-A-4 345 248. However since here three-pole switching elements (TFT's) are used all these electrodes must be provided on the same substrate, together with the switching devices and photo-sensitive elements. The use of these switches implies a continuous counterelectrode without the possibility of providing the scanning electrodes on the other substrate.

With the above structure, the wiring structure on the first substrate on which the active elements and the photo-sensitive elements are provided becomes simple, so that the first substrate with the wiring structure can be fabricated at a significantly high yield rate.

Also, by virtue of the combination of the two groups of scan electrodes into one group of common scan electrodes, what must be formed on the second substrate are the scan electrodes in the form of simple stripes, so that the second substrate with the circuit can be fabricated at a high yield rate. In addition, the common scan electrodes make it possible to perform processing for both display and input operations by the sequential driving of these scan electrodes. A logic circuit for the scan electrodes can therefore be simplified in structure, which may reduce the possibility of occurrence of errors in the display operation caused by the input operation and may provide a good and stable display.

According to the present invention, the photo-sensitive elements may be arranged so as to be responsive mainly to radiation other than visible radiation with a filter for blocking visible radiation being provided correspondingly to the photo-sensitive elements in the display device on a display screen side of the photo-sensitive elements. With this structure, each photo-sensitive element responds only to radiation out of the range

of the visible radiation, so that the input function can work in the normal surroundings and will not be adversely affected even when a display in full color is performed.

The invention will now be described with reference to the drawings in which:

Fig. 1 is a plan view of an enlarged portion of a substrate on the side of a signal electrodes in an embodiment of a display device according to the invention;

Fig. 2 is an illustration showing a cross section of the portion of Fig. 1 taken along the line II-II;

Fig. 3 is a circuit diagram of an equivalent circuit of each active element 1 on the substrate of Fig. 1;

Fig. 4 is a circuit diagram of an equivalent circuit of each photo diode 7 on the substrate of Fig. 1;

Fig. 5 is a plan view of an opposing substrate in the embodiment;

Fig. 6 is an illustration showing a cross section of the substrate of Fig. 5 taken along the line VI-VI;

Fig. 7 is an illustration showing one example of a color filter employed in the embodiment;

Fig. 8 is an illustration showing a partial cross section of the display device according to the embodiment;

Fig. 9 is a block diagram of a display and input control circuit in the embodiment in which the control circuit is connected to the respective electrodes on the substrate; and

Fig. 10 is a timing chart for explaining the operation of the display and input control circuit.

Figs. 1 and 2 show a substrate 10 which is disposed on one of the sides of a liquid crystal material in a liquid-crystal type color display device according to one embodiment of the invention, wherein Fig. 1 is a plan view of an enlarged part of the substrate 10 and Fig. 2 is a cross-sectional view of the substrate of Fig. 1 along the line II-II. In these figures, the width of each electrode is exaggerated in dimension. The substrate 10 is composed of a transparent material, such as a soda glass and a quartz glass, on which a number of pixel electrodes 9a, 9b,... each corresponding to a pixel are provided in the form of a matrix, for example, by patterning of an ITO layer.

Also provided on the substrate 10 are active elements 1a, 1b,... for driving the pixel electrodes, respectively. The active elements comprise semiconductor materials, such as a-Si and Se, and are formed each as a ring diode as shown in Fig. 3. Furthermore, the substrate 10 is provided thereon with signal electrodes 3a, 3b,... each for supplying a display signal to those active elements which correspond to a column of pixels (in Fig. 1, a column of pixels being those arranged in the vertical direction). These signal electrodes are also formed by subjecting a metal layer composed, for example, of ITO and Cr, to a patterning similarly to the case of the pixel electrodes.

The substrate 10 is further provided thereon with photo diodes (photo-sensitive elements) 7a, 7b,... for giving this display device an input function and with read-out electrodes 5a, 5b,... connected to these photodiodes 7. In this case, each photodiode 7 takes the form of a ring diode as shown in Fig. 4 and is formed simultaneously with the active elements 1a, 1b,..., that is to say, in the same process in which the active elements are formed. Each of the photodiodes 7 is formed per a predetermined number of pixel electrodes 9 (per 4 pixel electrodes, in Fig. 4). The read-out electrodes 5 are also formed simultaneously with the signal electrodes 3a, 3b, ...

As is apparent from Fig. 1, the wiring pattern on the substrate 10 comprises only signal electrodes 3a, 3b,... and the read-out electrodes 5a, 5b,... which are in parallel with the signal electrodes. The wiring pattern has thus no intersections and is very simple in structure. Therefore, the formation of the signal and read-out electrodes on the substrate 10 and that of the elements to be provided between these electrodes and the pixel electrodes are much easier, which will enhance the yield rate. In the process of production of the substrate 10, the band-gap of the a-Si, the condition for the formation of layers or the like is so determined with regard to the active elements that a leak of light to these elements is suppressed.

Figs. 5 and 6 show another substrate (opposing electrode) 11 which is disposed on the side opposite to the substrate 10 with the liquid crystal material being sandwiched therebetween. Fig. 5 is a plan view and Fig. 6 is a cross-section of the opposing substrate 11 in Fig. 5 along the line VI-VI. In these figures, the width of each electrode, for example, is exaggerated in dimension. The substrate 11 is provided thereon with scan electrodes 12a, 12b,... formed from a transparent conductive layer such as ITO, each scan electrode being correspondent to a row of pixel electrodes 9.

Fig. 7 is a plan view of a part of a color filter 16 which is provided on the opposing substrate 11 for a color display. This color filter 16 includes red (R) areas 17, green (G) areas 18 and blue areas 19. The remaining area 20 of the color filter 16 constitutes a black (BLK) area for absorbing visible rays. The color filter 16 is formed on the opposing substrate 11 in a known method such as deposition.

The aforesaid substrate 10, the opposing substrate 11 and the color filter 16 are assembled as shown in Fig. 8 to form the display device according to the present invention. In Fig. 8, denoted by a reference numeral 2 is the liquid crystal material (a display material) provided between the substrata 10 and 11, an denoted by reference numerals 31 and 32 are polarizing plates provided on the free surfaces of the substrata 11 and 10, respectively. In this case, the surface of this device on the side of the polarizing plate 31 is the front surface or the display surface. The display device is also provided at its rear with a back-light source (not shown) for illuminating

the device as indicated by an arrow B. Shown at 25 is a light pen which comprises a LED 26 for emitting a ray other than the visible rays, such as an infra-red ray. This infra-red ray is focused by a lens 27 to irradiate the display surface of the display device (see arrow A). The irradiating ray need not be focused too much. It is rather preferable to render the beam diameter two to three millimeters in order to ease the detection of the ray and to avoid erroneous operations of the active elements.

Fig. 9 is a block diagram of one example of a display and input control circuit for the above-described display device. The substrate 10 shown in Fig. 9 is so constructed that each photodiode 7 is provided per 6 x 8 pieces of pixel electrodes 9. In Fig. 9, the junction points between the active elements 1 and the signal electrodes 3 are indicated by dots on the electrodes 3, and the junction points between the photodiodes 7 and the read-out electrodes 5 are indicated by dots on the electrodes 5. The reason for the above construction is that any information, whether it is a pattern image or a character image, is actually displayed on a basis of display units each composed of several pieces of pixels (or dots), so that each photodiode 7 may be provided per several pieces of pixels rather than per a respective one of the pixels. In Fig. 9, shown at 30<sub>a1</sub>, 30<sub>a2</sub>,... and 30<sub>b1</sub>, 30<sub>b2</sub>,... are scan-electrode drive circuits for driving the scan electrodes 12 in accordance with an output from a control circuit 40. The circuits 30<sub>a1</sub>, 30<sub>a2</sub>,... drive the odd-numbered scan electrodes 12, and the circuits 30<sub>b1</sub>, 30<sub>b2</sub>,... drive the even-numbered scan electrodes. Also provided are signal-electrode drive circuits 38a, 38b,... which drive signal electrodes 3 in accordance with another output from the control circuit 40. The read-out electrodes 5 are connected to sampling circuits 39a, 39b,... which are provided for detecting an irradiated one of the photo-diodes 7. The control circuit 40 receives a picture signal S<sub>P</sub> and outputs a position-information signal S<sub>P</sub> representative of a detected position.

The display and input operation of the device having the above construction will now be described.

The display operation is effected by causing the scan-electrode drive circuit 30 to sequentially drive the scan electrodes 12 and by causing the signal-electrode drive circuit 38 to drive those signal electrodes 3 which correspond to the pixel electrodes 9 in the desired columns. The liquid crystal material is thus changed in state at its portions corresponding to the desired pixel electrodes, and a picture display is made by passing the back-light (indicated by the arrow B in Fig. 8) through the color filter 16 and the polarizing plate 31.

The input operation is achieved by irradiating, through the filter 16, the photodiode 7 at the desired position by the infra-red ray emitted from the light pen 25 shown in Fig. 8 to thereby rapidly decrease the resistance of the irradiated photodiode in accordance with its photo-conductivity. The change in resistance is detected by the sampling circuits 39, whereby the irradiated position or address is determined. The photodiodes at

those positions where no irradiation is made by the light pen 25 are not excited, because a light from the exterior is cut off by the visible-ray blocking area 20. Therefore, the resistance of each of these photodiodes does not change.

The operation of the above embodiment will now be described in more detail with reference to the timing chart of Fig. 10.

Shown at Y1, Y2,... are voltage waveforms of the scan signals applied to the scan electrodes 12 which are common to the active elements 1 for display and the photosensitive elements 7. Thus, the scan signals each having a voltage V<sub>a</sub> and a predetermined time length are sequentially applied to the scan electrodes 12. Shown at X is the display signal which is divided into pieces of an identical time length within each duration time of the scan voltage V<sub>a</sub> and applied sequentially to the signal electrodes 3.

The sampling of the photodiodes 7a, 7b,... for detection of their conductive states is performed in the following manner. The read-out electrodes 5a, 5b,... are supplied, within the duration time of each scan signal Y, sequentially with pulsed S1, S2,... each having a negative peak voltage V<sub>c</sub> and a positive peak voltage V<sub>b</sub>. During this time, it is determined whether a flowing-in current caused by each pulse of the voltage V<sub>c</sub> is present or not. In this case, the pulses of the voltage V<sub>b</sub> serve to perform the discharge operation.

In the above-described embodiments, a ring diode is employed as each active element for driving the pixel electrode. It will, however, be apparent that transistors can be used in the place of the ring diodes although this will result in a more complicated wiring pattern on the substrate 10.

In the case where a color display is not necessary, similar feature can be obtained by providing a filter area for blocking lights from the exterior only at the position of each photo-sensitive element.

As will be appreciated from the foregoing, with the structure of the display device according to the present invention, the electrodes to be formed on the opposing substrate are common to the display operation and the input operation, and are in the form of simple stripes. In addition, the signal electrodes and the read-out electrodes to be formed on the substrate, on which the active and photo-sensitive elements are formed, have no intersections and are thus simple in structure. It is therefore very easy to form the circuits on the respective substrata, which will make it possible to produce the display device at a high yield rate.

Furthermore, since the scan electrodes are common to the display and input functions, these electrodes can be driven by a simple logic circuit, which will avoid any confused operation in the logic circuits for the display and the sampling. The simple logic circuit can also avoid any possible errors in the display operation which will be caused by the input operation.

## Claims

1. A display device comprising a first substrate (10) provided with pixel electrodes (9) and active switching elements (1) for driving said pixel electrodes for picture display, photosensitive elements (7) comprising at least one semiconductor material which is the same as a semiconductor material included in the active elements and a group of read-out electrodes (5) and a display material (2) sandwiched between the first substrate and a second substrate (11) opposing the first substrate, characterized in that each photosensitive element is related to a predetermined number of pixel electrodes and the first substrate is further provided with a group of signal electrodes (3), which extend in either a row or a column direction of the pixel electrodes and are connected thereto via said switching elements (11) and which extend in the same direction as the read-out electrodes (5), the second substrate being provided with a group of scan electrodes (12) which extend in a direction perpendicular to the direction in which said signal electrodes extend, at least a number of scan electrodes being common to the photo-sensitive elements and pixels.
2. A display device as claimed in claim 1, characterized in that a photo-sensitive element is provided for at least two pixel electrodes.
3. A display device according to Claim 1 or 2 characterized in that each of said photo-sensitive elements is constructed so as to be sensitive mainly to radiation other than the visible radiation, and in that a filter for blocking the visible radiation is provided correspondingly to said photo-sensitive elements in said display device on a display screen side of said photo-sensitive elements.
4. A display device according to Claim 3, characterized in that said filter comprises colored areas each of which has one of the three primary colors and corresponds to a respective one of said pixel electrodes.
5. A display device according to any one of Claims 1 to 4, characterized by the provision of scanning means for sequentially driving said scan electrodes within each display period; signal-electrode driving means for sequentially driving said signal electrodes within a period of driving of each scan electrode in accordance with information of a picture to be displayed; read-out electrode driving means for sequentially driving in response to a sampling signal within the period of driving of each scan electrode; and detecting means for detecting, in accordance with currents which flow through said photo-sensitive elements in response to said sampling

signal, that one of said photo-sensitive elements which is receiving radiation.

## 5 Patentansprüche

1. Anzeigeanordnung, die ein erstes Substrat (10) mit Bildelementelektroden (9) und aktiven Schaltelementen (1) zum Ansteuern der Bildelektroden zur Bildwiedergabe enthält, wobei photoempfindliche Elemente (7) wenigstens ein Halbleitermaterial der aktiven Elemente und eine Gruppe von Auslese-Elektroden (5) aufweisen, und wobei ein Wiedergabematerial (2) zwischen dem ersten Substrat und dem zweiten, dem ersten Substrat gegenüberliegenden Substrat (11) vorgesehen ist, dadurch gekennzeichnet, daß jedes photoempfindliche Element für eine vorgegebene Anzahl von Bildelementelektroden vorgesehen und zwischen einer Auslese-Elektrode und einer Bildelementelektrode in Reihe geschaltet ist und wobei das erste Substrat außerdem mit einer Gruppe von Signalelektroden (3) versehen ist, die sich in einer Zeilen- oder Spaltenrichtung der Bildelementelektroden erstrecken und damit über die Schaltelemente (1) verbunden sind, und die sich in derselben Richtung wie die Auslese-Elektroden (5) erstrecken, wobei das zweite Substrat mit einer Gruppe von Abtastelektroden (12) versehen ist, die sich in einer Richtung senkrecht zur Richtung der Signalelektroden erstrecken, wobei die genannten Abtastelektroden mit den photoempfindlichen Elementen verbundenen Bildelektroden sowie Bildelektroden zur Bildwiedergabe gemeinsam sind.
2. Anzeigeanordnung nach Anspruch 1, dadurch gekennzeichnet, daß für wenigstens zwei Bildelementelektroden ein photoempfindliches Element vorgesehen ist.
3. Anzeigeanordnung nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß jedes der photoempfindlichen Elemente derart aufgebaut ist, daß es hauptsächlich für andere als sichtbare Strahlung empfindlich ist, und daß ein Filter zum Abblocken der sichtbaren Strahlung dementsprechend bei den photoempfindlichen Elementen in der Anzeigeanordnung an einer Anzeigeschirmseite der photoempfindlichen Elemente angebracht ist.
4. Anzeigeanordnung nach Anspruch 3, dadurch gekennzeichnet, daß das Filter farbige Gebiete enthält, von denen jedes eine der drei Primärfarben enthält, und einer der Bildelementelektroden entspricht.
5. Anzeigeanordnung nach einem oder mehreren der vorangehenden Ansprüche 1 bis 4, dadurch ge-

kennzeichnet, daß ein Abtastmittel zum sequentiellen Ansteuern der Abtastelektroden in jeder Anzeigepériode, ein Signalelektrodensteuermittel zum sequentiellen Ansteuern der Signalelektroden in einer Antriebsperiode jeder Abtastelektrode entsprechend den Daten eines anzuzeigenden Bildes, ein Auslese-Elektrodensteuermittel zum sequentiellen Ansteuern in Beantwortung eines Abtastsignals in der Antriebsperiode jeder Abtastelektrode und ein Detektormittel zum Detektieren jenes der photoempfindlichen Elemente, das Strahlung empfängt, entsprechend den photoempfindlichen Elementen in Beantwortung des Abtastsignals durchfließenden Strömen vorgesehen sind.

### Revendications

1. Dispositif d'affichage comprenant un premier substrat (10) pourvu d'électrodes de pixels (9) et d'éléments de commutation actifs (1) pour exciter lesdites électrodes d'image, des éléments photosensibles (7) comprenant une matière qui est similaire à une des matières utilisées dans les éléments actifs et un groupe d'électrodes de lecture (5) et une matière d'affichage (2) prise en sandwich entre le premier substrat et un deuxième substrat (11) opposé au premier substrat, caractérisé en ce que chaque élément photosensible est rapporté à un nombre prédéterminé d'électrodes de pixels et le premier substrat est, en outre, pourvu d'un groupe d'électrodes de signal (3), qui s'étendent dans la direction d'une rangée ou d'une colonne des électrodes de pixels et y sont connectées via lesdits éléments de commutation (1) et qui s'étendent dans la même direction que les électrodes de lecture (5), le deuxième substrat étant pourvu d'un groupe d'électrodes de balayage (12) qui s'étendent dans une direction perpendiculaire à la direction dans laquelle lesdites électrodes de signal s'étendent, au moins un certain nombre d'électrodes de balayage étant communes aux éléments photosensibles et aux pixels.
2. Dispositif d'affichage selon la revendication 1, caractérisé en ce qu'un élément photosensible est prévu pour au moins deux électrodes de pixels.
3. Dispositif d'affichage selon la revendication 1 ou 2, caractérisé en ce que chacun desdits éléments photosensibles est construit de manière à être sensible principalement à un rayonnement autre que le rayonnement visible, et en ce qu'un filtre permettant de bloquer le rayonnement visible est disposé, en correspondance avec lesdits éléments photosensibles, dans le dispositif d'affichage du côté écran d'affichage desdits éléments photosensibles.
4. Dispositif d'affichage selon la revendication 3, ca-

ractérisé en ce que ledit filtre comprend des zones colorées qui ont chacune l'une des trois couleurs primaires et correspondent à une desdites électrodes de pixels.

5. Dispositif d'affichage selon l'une quelconque des revendications 1 à 4, caractérisé par la présence de moyens de balayage pour exciter en séquence lesdites électrodes de balayage à l'intérieur de chaque période d'affichage; de moyens d'excitation des électrodes de signal pour exciter en séquence lesdites électrodes de signal dans une période d'excitation de chaque électrode de balayage conformément aux informations d'une image à afficher; de moyens d'excitation des électrodes de lecture pour exciter en séquence lesdites électrodes de lecture en réaction à un signal d'échantillonnage à l'intérieur de la période d'excitation de chaque électrode de balayage; et de moyens de détection pour détecter, conformément à des courants qui s'écoulent à travers lesdits éléments photosensibles en réaction audit signal d'échantillonnage, celui des éléments photosensibles qui reçoit le rayonnement.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7






FIG. 8




FIG. 9




FIG. 10